

Product **Contacts: 3 DIN, male panel mount connector, solder, silver plated contacts, UL approval**


Area **M16 IP67 Series 423/ 723/ 425**

Article number **09 0107 00 03**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,50	0,00
2	0,00	3,50
3	-3,50	0,00

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design	male panel mount connector
Connector locking system	bolted
Termination	solder
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	20
Upper temperature	95 °C
Lower temperature	-40 °C

Cable data

Approval 1	UL
------------	----

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	7 A
Volume resistivity	≤ 5 mΩ
EMV compliance	shielded
Degree of protection	IP67

Material

Material of contact	CuZn (Messing)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)

Product

Contacts: 3 DIN, male panel mount connector, solder, silver plated contacts, UL approval

Area

M16 IP67 Series 423/ 723/ 425

Article number

09 0107 00 03

Installation instructions / Mounting cutout

