

Product **Contacts: 4, male panel mount connector, rectangular flange, with single wires**


Area **M16 IP67 Series 423/ 723/ 425**

Article number **09 0111 320 04**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,32	-1,08
2	2,05	2,83
3	-2,05	2,83
4	-3,32	-1,08

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design male panel mount connector

Connector locking system bolted

Termination single wires

Wire gauge (mm) 0,75 mm²

Wire gauge (AWG) 22

Upper temperature 95 °C

Lower temperature -40 °C

Electrical parameters

Rated voltage 300 V

Rated impulse voltage 1500 V

Pollution degree 1

Overvoltage category I

Material group II

Rated current (40°C) 5 A

Volume resistivity ≤ 5 mΩ

Degree of protection IP67

Mechanical operation > 500 Mating cycles

Material

Material of contact CuSn (Bronze)

Contact plating Ag (silver)

Material of contact body PBT (UL 94 V-0)

Product

Contacts: 4, male panel mount connector, rectangular flange, with single wires

Area

M16 IP67 Series 423/ 723/ 425

Article number

09 0111 320 04

Installation instructions / Mounting cutout

