

Product	Contacts: 4, female panel mount connector, rectangular flange, with single wires
Area	M16 IP67 Series 423/ 723/ 425
Article number	09 0112 320 04


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,32	-1,08
2	2,05	2,83
3	-2,05	2,83
4	-3,32	-1,08

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design	female panel mount connector
Connector locking system	bolted
Termination	single wires
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	22
Upper temperature	95 °C
Lower temperature	-40 °C

Electrical parameters

Rated voltage	300 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	II
Rated current (40°C)	5 A
Volume resistivity	≤ 5 mΩ
Degree of protection	IP67
Mechanical operation	> 500 Mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)

Product

Contacts: 4, female panel mount connector, rectangular flange, with single wires

Area

M16 IP67 Series 423/ 723/ 425

Article number

09 0112 320 04

Installation instructions / Mounting cutout

