

Product **Contacts: 5 Stereo, female angled connector, cable outlet 4 - 6 mm, plastic model, silver plated contacts**


Area **M16 IP40 Series 682**

Article number **09 0142 70 05**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	-3,50	0,00
2	0,00	3,50
3	3,50	0,00
4	-2,47	2,47
5	2,47	2,47

You can find the item description on the next page.

Technical data

General features

Connector Design female angled connector

Connector locking system bolted

Termination solder

Wire gauge (mm) 0,75 mm²

Wire gauge (AWG) 20

Cable outlet 4 - 6 mm

Upper temperature 85 °C

Lower temperature -40 °C

Electrical parameters

Rated voltage 60 V

Rated impulse voltage 500 V

Pollution degree 1

Overvoltage category I

Material group III

Rated current (40°C) 6 A

Volume resistivity ≤ 5 mΩ

EMV compliance not shielded

Degree of protection IP40

Material

Material of contact CuSn (Bronze)

Contact plating Ag (silver)

Material of contact body PBT (UL 94 V-0)

Product	Contacts: 5 Stereo, female angled connector, cable outlet 4 - 6 mm, plastic model, silver plated contacts
Area	M16 IP40 Series 682
Article number	09 0142 70 05

Item description

