

Product **Contacts: 4, male panel mount connector, crimp**


Area **M16 IP40 Series 581/ 680/ 682**

Article number **09 0311 700 04**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,32	-1,08
2	2,05	2,83
3	-2,05	2,83
4	-3,32	-1,08

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design male panel mount connector
 Connector locking system bolted
 Termination crimp
 Wire gauge (mm) siehe Crimpkontakte unter Zubehör
 Cable outlet -
 Upper temperature 85 °C
 Lower temperature -40 °C

Electrical parameters

Rated voltage 250 V
 Rated impulse voltage 1500 V
 Pollution degree 1
 Overvoltage category I
 Material group III
 Rated current (40°C) 6 A
 Volume resistivity ≤ 5 mΩ
 EMV compliance not shielded
 Degree of protection IP40
 Mechanical operation > 500 Mating cycles

Material

Material of contact CuZn (Messing)
 Contact plating Ag (silver)
 Material of contact body PBT (UL 94 V-0)

Product

Contacts: 4, male panel mount connector, crimp

Area

M16 IP40 Series 581/ 680/ 682

Article number

09 0311 700 04

Installation instructions / Mounting cutout

