

Product **Contacts: 4, male panel mount connector, dip-solder, screwed from front**
 Area **M9 IP67 Series 712/702**
 Article number **09 0411 90 04**

Illustration	Scale drawing	Contact Arrangement															
		<table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1,10</td> <td>-1,10</td> </tr> <tr> <td>2</td> <td>1,10</td> <td>1,10</td> </tr> <tr> <td>3</td> <td>-1,10</td> <td>1,10</td> </tr> <tr> <td>4</td> <td>-1,10</td> <td>-1,10</td> </tr> </tbody> </table>		X	Y	1	1,10	-1,10	2	1,10	1,10	3	-1,10	1,10	4	-1,10	-1,10
	X	Y															
1	1,10	-1,10															
2	1,10	1,10															
3	-1,10	1,10															
4	-1,10	-1,10															

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design	male panel mount connector
Connector locking system	bolted
Termination	dip-solder
Wire gauge (mm)	-
Wire gauge (AWG)	-
Cable outlet	-
Upper temperature	85 °C
Lower temperature	-40 °C

Electrical parameters

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	II
Material group	III
Rated current (40°C)	3 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shieldable
Degree of protection	IP67
Mechanical operation	> 500 Mating cycles

Material

Material of contact	CuZn (Messing)
Contact plating	Au (gold)
Material of contact body	PA (UL 94 V-0)

Product **Contacts: 4, male panel mount connector, dip-solder, screwed from front**

Area **M9 IP67 Series 712/702**
Article number **09 0411 90 04**

Installation instructions / Mounting cutout

