


Product	Contacts: 4+PE, Fixing thread: PG 11, male panel mount connector with single wires and UL approval
Area	7/8" Series 820/870
Article number	09 2451 310 05


Illustration



Scale drawing



Contact Arrangement



- 1 schwarz/black
- 2 blau/blue
- PE grün/gelb/green/yellow
- 4 braun/brown
- 5 weiß/white

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design	male panel mount connector
Connector locking system	bolted
Termination	single wires
Wire gauge (mm)	0,82 mm ²
Wire gauge (AWG)	18
Upper temperature	85 °C
Lower temperature	-25 °C

Electrical parameters

Rated voltage	300 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	III
Material group	III
Rated current (40°C)	8 A
Volume resistivity	≤ 5 mΩ
EMV compliance	not shielded
Degree of protection	IP67
Mechanical operation	> 100 Mating cycles

Material

Material of contact	CuZn (Messing)
Contact plating	Au (gold)
Material of contact body	PUR (UL 94 HB)


Product **Contacts: 4+PE, Fixing thread: PG 11, male panel mount connector with single wires and UL approval**

Area **7/8" Series 820/870**

Article number **09 2451 310 05**


Installation instructions / Mounting cutout

Mit Durchgangsbohrung/With bore hole




alternativ/alternativ

Mit Gewinde, einschraubbar/With thread to screw in




	A	B	C	D	E
PG11	PG11	20,2	18,7	20,2	17,0
PG13,5	PG13,5	22,0	20,5	22,0	18,8
M20x1,5	M20x1,5	21,6	20,1	21,6	17,8

Mit Durchgangsbohrung/With bore hole
von vorn verschraubbar/front fastened



alternativ/alternativ

Mit Gewinde, einschraubbar/With thread to screw in



A	B	C	D	E
7/8-16UN-20	23	22,4	23,9	20,2
M26x1,5	27,3	26,2	27,7	24,2