


Product **Contacts: 8, male panel mount connector**
Area **Bayonet IP40 Series 710**
Article number **09 9481 00 08**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	0,90	-1,65
2	1,85	-0,35
3	1,45	1,20
4	0,00	1,85
5	-1,45	1,20
6	-1,85	-0,35
7	-0,90	-1,65
8	0,00	0,00

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design male panel mount connector
Connector locking system Bayonet
Termination solder
Wire gauge (mm) 0,14 mm²
Wire gauge (AWG) 26
Cable outlet -
Upper temperature 85 °C
Lower temperature -40 °C

Electrical parameters

Rated voltage 125 V
Rated impulse voltage 1500 V
Pollution degree 1
Overvoltage category II
Material group III
Rated current (40°C) 1 A
Volume resistivity ≤ 3 mΩ
EMV compliance Shielding is not possible
Degree of protection IP40
Mechanical operation > 500 Mating cycles

Material

Material of contact CuZn (Messing)
Contact plating Au (gold)
Material of contact body PA (UL 94 V-0)

Product

Contacts: 8, male panel mount connector

Area

Bayonet IP40 Series 710

Article number

09 9481 00 08

Installation instructions / Mounting cutout

