



Product	Contacts: 3, cable: 3 x 1,5 PUR, female cable connector, cable length: 5m
Area	7/8" Series 870
Article number	77 1430 0000 50003-0500

Scale drawing



Contact Arrangement



Technical data

General features

Connector Design	Female cable connector
Connector locking system	bolted
Wire gauge (mm)	1,50 mm ²
Wire gauge (AWG)	(16)
Upper temperature	85 °C
Lower temperature	-25 °C

Cable data

material housing	PUR
Insulation single lead	TPM
Single lead structure	82 x 0,15
Cable sheath Ø	7.4
Temperature range cable movable °C from	-20
Temperature range cable movable °C to	80
Temperature range cable fixed °C from	-50
Temperature range cable fixed °C to	80
Bending radius cable fixed	-
Bending radius cable movable	7,5 x d
Approval 1	UL listed
Cable diameter	7.4

Electrical parameters

Rated voltage	300 V
Rated impulse voltage	4000 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	12 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP68
Mechanical operation	> 100 Mating cycles

Material

Material of contact	CuZn (Messing)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR