


Product	Contacts: 4, Cable outlet: 4 - 6 mm, male angled connector, metal lock, screw terminal connection, UL approval
Area	M12-B Series 715
Article number	99 0429 135 04


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	2,50	0,00
2	0,00	2,50
3	-2,50	0,00
4	0,00	-2,50

You can find the item description and assembly instruction on the next page.

Technical data

General features

Connector Design	male angled connector
Connector locking system	bolted
Termination	screw
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	18-20
Cable outlet	4 - 6 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Electrical parameters


Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 8 mΩ
EMV compliance	not shielded
Degree of protection	IP67
Mechanical operation	> 50 Mating cycles

Material

Material of contact	CuZn (Messing)
Contact plating	CuSnZn (optalloy)
Material of contact body	PA

Product	Contacts: 4, Cable outlet: 4 - 6 mm, male angled connector, metal lock, screw terminal connection, UL approval
Area	M12-B Series 715
Article number	99 0429 135 04

Item description



Installation instructions / Mounting cutout

