Product sheet


Miniature

Product	**Contacts: 3 DIN, male angled connector, cable outlet 6 - 8 mm**
Area	**Bayonet IP40 Series 678**
Article number	**99 0605 72 03**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,50	0,00
2	0,00	3,50
3	-3,50	0,00

You can find the item description on the next page.

Technical data

General features

Connector Design	male angled connector
Connector locking system	Bayonet
Termination	solder
Wire gauge (mm)	0,75 mm²
Wire gauge (AWG)	20
Cable outlet	6 – 8 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	7 A
Volume resistivity	≤ 5 mΩ
EMV compliance	not shielded
Degree of protection	IP40

Material

Material of contact	CuZn (Messing)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)

Product sheet

Miniature

Product	**Contacts: 3 DIN, male angled connector, cable outlet 6 - 8 mm**
Area	**Bayonet IP40 Series 678**
Article number	**99 0605 72 03**

Item description

