

Product **Contacts: 4+PE, female cable connector with VDE and ETS approval, cable outlet 10 - 12 mm**


Area **RD30 Power Series 694**

Article number **99 0710 00 05**


Illustration



Scale drawing




Contact Arrangement



	X	Y
1	4,77	-4,77
2	4,77	4,77
3	-4,77	4,77
4	-4,77	-4,77
⊕	0,00	0,00

Attenuation characteristics



You can find the item description on the next page.

Technical data

General features

Connector Design	Female cable connector
Connector locking system	bolted
Termination	screw
Wire gauge (mm)	2,50 mm ²
Wire gauge (AWG)	14
Cable outlet	10 - 12 mm
Upper temperature	100 °C
Lower temperature	-40 °C

Cable data

Approval 1	ESTI+
Approval 2	VDE

Electrical parameters

Rated voltage	400 V
Rated impulse voltage	6000 V
Pollution degree	3
Overvoltage category	III
Material group	III
Rated current (40°C)	20 A
Volume resistivity	≤ 5 mΩ
EMV compliance	not shielded
Degree of protection	IP65
Mechanical operation	> 50 Mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Ag (silver)
Material of contact body	PA (UL 94 HB)

Product

Contacts: 4+PE, female cable connector with VDE and ETS approval, cable outlet 10 - 12 mm

Area

RD30 Power Series 694

Article number

99 0710 00 05

Item description

