


Product **Contacts: 3, female cable connector, cable outlet 3 -4 mm**
Area **Bayonet IP40 Series 710**
Article number **99 0976 100 03**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	-1,55	0,00
2	0,00	1,55
3	1,55	0,00

You can find the item description on the next page.

Technical data

General features

Connector Design	Female cable connector
Connector locking system	Bayonet
Termination	solder
Wire gauge (mm)	0,25 mm ²
Wire gauge (AWG)	24
Cable outlet	3 - 4 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Electrical parameters

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	II
Material group	III
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	Shielding is not possible
Degree of protection	IP40
Mechanical operation	> 500 Mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (gold)
Material of contact body	PA (UL 94 V-0)

Product	Contacts: 3, female cable connector, cable outlet 3 -4 mm
Area	Bayonet IP40 Series 710
Article number	99 0976 100 03

Item description

