


Product	Contacts: 4, cable plug connector with solder eye, shieldable, cable outlet 4 - 6 mm, gold plated contacts
Area	M16 IP40 Series 581
Article number	99 2009 09 04


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,32	-1,08
2	2,05	2,83
3	-2,05	2,83
4	-3,32	-1,08

You can find the item description on the next page.

Technical data

General features

Connector Design	Cable Connector
Connector locking system	bolted
Termination	solder
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	20
Cable outlet	4 – 6 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	6 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shielded
Degree of protection	IP40

Material

Material of contact	CuZn (Messing)
Contact plating	Au (gold)
Material of contact body	PBT (UL 94 V-0)

Product **Contacts: 4, cable plug connector with solder eye, shieldable, cable outlet 4 - 6 mm, gold plated contacts**

Area **M16 IP40 Series 581**
Article number **99 2009 09 04**

Item description

