


Product description	M8 male cable connector, Contacts: 5, unshielded, moulded on cable, IP67, UL listed, PVC grey, 5 x 0.34 mm ²
Area	M8 series 718
Order number	77 3405 0000 20005-0500


Illustration



Scale drawing



Contact arrangement (Plug-in side)



Technical data

General features

Order number	77 3405 0000 20005-0500
Notice	Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right.
Connector design	male cable connector
Cable length	5 m
Version	connector male straight
Connector locking system	screw
Termination	moulded on cable
Degree of protection	IP67
Cross-sectional area	0.34 mm ² / AWG 22
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Customs tariff number	85444290

Electrical parameters

Rated voltage	30 V
Rated impulse voltage	800 V
Rated current (40 °C)	3 A
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	PUR
Contact body material	PUR
Contact material	CuZn (brass)
Contact plating	Au (gold)
Locking material	Zinc die-cast nickel-plated
REACH SVHC	CAS 7439-92-1 (Lead)

Authorization/approvals

Approval 1	UL listed
------------	-----------

Classifications

eCl@ss 11.1	27-06-03-11
ETIM 7.0	EC001855

Declarations of conformity

RoHS Directive	2011/65/EU (EN 50581:2012)
----------------	----------------------------

Product description	M8 male cable connector, Contacts: 5, unshielded, moulded on cable, IP67, UL listed, PVC grey, 5 x 0.34 mm ²
Area	M8 series 718
Order number	77 3405 0000 20005-0500

Technical data

Cable data

Cable diameter	5.2 mm
Cross section	5 x 0.34 mm ²
Sheath material	PVC
Single-lead insulation	PVC
Single-lead structure	42x0.1 mm
Cable color	grey
Conductor resistance	60Ω/Km
Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø
Bending cycles	>2Mio.
Permitted acceleration	5 m/s ² +1 m/s ²
Travel distance, horizontal	5 m/sec ² -> 5m
Travel distance, vertical	5 m/sec ² -> 2m
Travel speed	≤ 200 m/min (5 m horizontal distance)
Temperature range cable in move from/to	-5°C / +105°C
Temperature range cable fixed from/to	-40°C / +105°C
Halogen free	No

Product description	M8 male cable connector, Contacts: 5, unshielded, moulded on cable, IP67, UL listed, PVC grey, 5 x 0.34 mm ²
Area	M8 series 718
Order number	77 3405 0000 20005-0500

Security notices

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Plug connectors with enclosure protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre. To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).